


DS-100 doors combine versatility, dependability.



- 1** *Corrugated door curtain*, available in round or square profile, is hot-dipped, galvanized 26-Ga. steel, primed then finished with high gloss, silicone polyester paint.
- 2** *Polypropylene anti-wear strips* come factory-installed as continuous guides for sliding metal parts, providing quieter operation and longer service life.
- 3** *Rigid support bracket with bearings* hold constant door tension, and allow easy adjustments.
- 4** *Bottom bar assembly* includes heavy-duty steel angle, extruded aluminum bottom bar and replaceable tubular-type vinyl astragal.
- 5** *Slide-bolt assemblies* fabricated of heavy-duty steel lock the closed door from inside at the bottom corners (not shown; door has optional mini curtain lock.) For added security, both slide bolts accept padlocks.
- 6** *Roll-up door guides* are 18-Ga. galvanized steel, 2" wide. DS-100 guides install to masonry, steel or wood construction equally well.
- 7** *Automatic door stops* prevent door from rolling up past the header.
- 8** *Oil-tempered steel spring* is engineered to counterbalance different door sizes and weights for smooth, easy operation. The spring is shot peened to increase strength and add cycle life to the spring.
- 9** *Heavy-duty steel axle* supports door curtain and counterbalance system.



Optional Tension-Pro™ Adjustable Spring Device allows adjustments to be made to the counterbalance easily and safely. No special tools are needed. No pins to align. No risk of tension being released accidentally. U.S. Patent #6,527,037



Standard support brackets include anti-friction bearings.



Optional door insulation features two layers of aluminum mylar film laminated to two

layers of heavy-duty polyethylene air-bubble material. Its "R"-value of 4 helps control heat gain/loss. Includes flexible vinyl top and side draft stops as weather seals between the door and the building.



Optional mini curtain lock allows access from outside. Designed for owner/tenant security. Rust resistant.

20 Year Warranty Against Chalk and Fade



10 Year Warranty Against Chalk and Fade

Warranty: Wayne-Dalton Corp. and its subsidiaries back all of their doors and fittings with a LIMITED WARRANTY against defects in materials and workmanship. Paint has a limited warranty to hold up against weather induced chipping, cracking, and peeling for 25 years. Refer to each color for the number of years warranted not to chalk or change color. A copy of this warranty is available upon request.

Because of continuing product improvements, we reserve the right to change the product specifications and designs without prior notice.